

# SHARP®

## Notevision M25X



PG-M25X Wireless Projector

**NOW WITH WIRELESS NETWORK CONNECTIVITY**

### SPECIFICATIONS

Resolution	XGA (1024 x 768) up to UXGA (1600 x 1200)
TV Lines	700 TV Lines (HDTV 720 P)
Device Type	0.7" DDR 12° DMD™
H & V Frequency	fh 15 - 126 kHz /fv 43 - 200 Hz
Dot Clock	12 - 230 MHz
Compatibility	PC, Mac and Work Station
Video System	NTSC/PAL/PAL-N/PAL-M/SECAM/NTSC 4.43
Resizing	ImageACE Resizing
Brightness	1900 ANSI Lumens w/ 85% CCR
Contrast Ratio	1000:1 Full On / Off; 800:1 ANSI
Lens Type	Fujinon 1.2:1 Manual Zoom / Focus
Aspect Ratio	4:3 & 16:9
Remote Control	RF Gyro Remote
Audio System	2.0 Watt Monaural
Lamp	DC 210 Watt SHP, User-replaceable/2000 Hours
Lamp Module Part No.	BQC-PGM20X//1
Fan Noise	37 dB
Power Source	100-240 VAC, 50/60Hz
Power Consumption	295 Watts / 255 watts (power save)
Heat Dissipation	1110 BTU / Hour
Dimensions (w x h x d)	8 5/8" x 3" x 11 15/16"
Weight	5.8 lbs.
Limited Warranty	3 Years Parts/Labor & 2 Years Sharp Express Repair, Lamp 90 Days

Sharp's wireless Notevision M25X (PG-M25X) is among the smallest, lightest, and highest performing projectors in the Mobile Category! The M25X weighs **5.8 pounds**, and despite its sleek, compact size, provides **1900 ANSI Lumens** brightness and high quality data images in a wireless environment.

The Notevision M25X offers wireless capabilities with IEEE802.11b wireless LAN technology and high image quality with newly developed vector quantization (VQ) technology. A PCMCIA card slot allows for memory card presentations with the wireless RF GyroRemote. **The M25X can also directly communicate with wireless access points, thus allowing users to directly access corporate LAN's wirelessly, open files and simultaneously project those images.**

Advanced features such as exclusive CV-IC System II, sRGB color management for accurate color rendition and 3x speed color wheel for elimination of flicker all contribute to superior image quality.

The Notevision M25X boasts built-in computer and video inputs, audio system, high speed AutoSync for automatic image setup and digital keystone correction. Choose the Notevision M25X for high-end "XGA" resolution, providing a full 1024 x 768 native resolution. Outstanding PC compatibility supports 200 Hz refresh rate and up to UXGA resolution (1600 x 1200 pixels) with Intelligent ImageACE Resizing.

The M25X is backed by a limited three-year parts and labor warranty including two years, at no charge, Sharp ER Service, a 24-hour turnaround express repair program to ensure maximum reliability and peace of mind.

Notevision M25X. Everything a presenter should be.

### ADVANCED FEATURES

- \* Communicate with wireless access points
- \* Wireless image transfer
- \* Memory card playback
- \* Password start-up / theft deterrent
- \* 1900 ANSI Lumen Brightness
- \* International Power Supply (100-240V AC) with power save mode
- \* Digital Keystone Correction up to +/-35°
- \* Support for 1080i, 720p, 480p Component Video and 480i
- \* 1.2:1 Manual Zoom/Focus Lens
- \* New CV-IC System II plus sRGB color management
- \* One-step custom start-up image
- \* GyroRemote control with mouse control

### PROJECTION DISTANCES

Screen Diagonal	Screen Width	Screen Height	Minimum Distance	Maximum Distance
40"	32"	24"	5'2"	6'3"
60"	48"	36"	7'9"	9'5"
72"	58"	43"	9'4"	11'4"
84"	67"	50"	10'11"	13'3"
100"	80"	60"	13'1"	15'10"
150"	120"	90"	19'8"	23'9"
200"	160"	120"	26'3"	31'9"
250"	200"	150"	32'10"	39'8"
300"	240"	180"	39'5"	--

APPROXIMATE PROJECTION DISTANCE FROM SCREEN TO FRONT OF LENS

### INPUTS/OUTPUTS

- Input 1** - DVI-I (29pin) digital, computer (RGB), and component
- Input 2** - S-Video (4 Pin DIN)
- Input 3** - Composite (RCA)
- Input 4** - PCMCIA TypeII (PC Card Slot)
- 1 - Audio Input - 3.5mm Stereo Minijack
- 1 - USB Port (4 Pin)
- 1- Wired Remote Control Input

### INCLUDED ACCESSORIES

Gyro Remote Control, Four AAA Size Batteries, 6' Power Cord, 6' USB Mouse Control Cable, 6' DVI to 15 pin HD cable, Projector Operation Manual, Projector Quick Reference Guide, Carry Bag, (2) IEEE802.11b Wireless Cards

### OPTIONAL ACCESSORIES

- AN-M200PCBAG** Soft Sided Carry-on Bag (Projector & PC)
- AN-M200SC** Hard Sided Shipping Case w/wheels & handle
- AN-M100WB** Hard Sided Bag w/wheels (Projector & PC)
- AN-PGCM90** Ceiling bracket for PG-M25X
- AN-EP101B** Extension Pole
- AN-CMCSS15** Security System for use without AN-EP101B
- AN-CMCSS46** Security System for use with AN-EP101B
- AN-A1DV** DVI to 15 pin D-Sub Adapter (8")
- AN-A1MY** Monitor Loop-Out Adapter (8")
- AN-C3DV** DVI Digital Cable (10')
- AN-C3BN** 5 BNC to 15 pin D-Sub cable (10')
- AN-WC11B** IEEE802.11b wireless card

Design and specifications are subject to change without notice. All trademarks are property of their respective holders.

SHARP ELECTRONICS CORPORATION  
LCD Products Group, Sharp Plaza, Mahwah, NJ 07430-2135  
1-888-GO-SHARP (1-888-467-4277)  
E-mail: ProLCD@SharpSEC.com  
www.SharpLCD.com



**SHARP**  
be sharp™

